

Non-asbestos Sealing Materials

无石棉密封材料

TL1404

产品说明

该产品为通用型灰色无石棉密封材料，含丁腈橡胶，具有良好的压缩回弹性和油密封性，间隙使用温度在180℃以下。材料使用成本较低。

物理性能

| 项目 | 指标 |
|----------------------------|------------|
| 密度/(g/cm ³) | ≥ 1.30 |
| 拉伸强度/Mpa | ≥ 7.0 |
| 压缩率/% | 15-30 |
| 回弹率/% | ≥ 30 |
| 浸渍IRM903油后性能 149±2℃, 5h | 增重率/% ≤ 60 |
| | 增厚率/% ≤ 22 |
| 浸渍ASTM燃油B后性能 21~30℃, 5h | 增重率/% ≤ 50 |
| | 增厚率/% ≤ 22 |

Description

TL1404 is a gray color economic Non-asbestos vulcanized gasket material for general application. It contains nitrile butadiene rubber binder. And it has good oil resistant performance, good compressibility and recovery. The short duration maximum temperature is up to 180℃ (356°F).

Technical Specifications

| Property | Specification |
|---|--------------------------|
| Density/(g/cm ³) | ≥ 1.30 |
| Tensile Strength /Mpa | ≥ 7.0 |
| Compressibility /% | 15-30 |
| Recovery /% | ≥ 30 |
| Fluid Resistance (at ASTM IRM 903 Oil, 149±2℃, 5h) | Weight Change /% ≤ 60 |
| | Thickness Change /% ≤ 22 |
| Fluid Resistance (at ASTM Fuel B, 21-30℃, 5h) | Weight Change /% ≤ 50 |
| | Thickness Change /% ≤ 22 |

天府密封科技

TEAMFUL SEALING TECHNOLOGY

总公司:

成都天府垫片科技有限公司
地址: 中国·四川省成都市双流县西南
航空港经济技术开发区双华路三段123号
电话: 86-028-85875538
传真: 86-028-85651433
邮件: sales@teamful.net

出口部:

电话: 86-028-85875509
传真: 86-028-85651433
邮件: qul@teamful.net

广东分公司

江门天府密封科技有限公司
地址: 中国·广东省江门市新会区大泽
镇创利来工业基地泽棠路
电话: 86-0750-6805518
传真: 86-0750-6805519
邮件: sales@teamfulgd.net

Teamful Headquarters

Chengdu Teamful Gasket Technology
Co.,Ltd.
ADD: No.123, Shuanghua Road Section 3,
the Southwest Airport Economic
Development Zone, Shuangliu, Chengdu,
P.R. China
Tel: 86-028-85875538
Fax: 86-028-85651433
Email: sales@teamful.net

Foreign Trade Dept.

电话: 86-028-85875509
传真: 86-028-85651433
邮件: qul@teamful.net

Guangdong Teamful Branch

JiangMen Teamful Sealing Technology
Co.,Ltd.
ADD: Zetang Road, Chuanglilai Industrial
Zone, Daze Town, Xinhui District, Jiangmen
City, Guangdong, P.R.China
TEL: 86-0750-6805518
FAX: 86-0750-6805519
Email: sales@teamfulgd.net